



- NOTES: - ALL RESISTORS IN OHMS $\frac{1}{2}$ W 10% UNLESS OTHERWISE SPECIFIED.
 - ALL CAPACITORS IN MFD. & 400V UNLESS OTHERWISE SPECIFIED.
 - D.C. VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20000 Ω PER VOLT VOLTMETER.
 - NUMBERS IN PARENTHESIS REFER TO AMPGSS PART NO.
 - PARTS DESIGNATED BY * ARE IN 240V MODELS ONLY. THE P.T. FOR 240V MODELS HAS BLK WIRE CONNECTED TO BLUE WIRE.
 - D.C. VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO CHASSIS GROUND UNLESS OTHERWISE SPECIFIED.
 - CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.
 - 07-10 ARE SILICON AX TYPE 1AMP 1400 VOLTS DIODES.



MODEL
V2
U.S. PATENT PENDING.
 DRN BY DATE DWG. NO. PART NO. REV.
 G.C. 671 06800 400268 B