



NOTES

- ALL RESISTORS IN OHMS $\frac{1}{2}$ W, 10% UNLESS OTHERWISE SPECIFIED.
- ALL CAPACITORS IN MFD. & 400V UNLESS OTHERWISE SPECIFIED.
- DC VOLTAGE READINGS WITH NO SIGNAL APPLIED USING A 20000 Ω PER VOLT VOLTMETER.
- NUMBERS IN PARENTHESIS REFER TO AMP'S PART NO.
- PARTS DESIGNATED BY * ARE IN 240V MODELS ONLY, THE P-1 FOR 240V MODELS HAS THICK WIRE CONNECTED TO BLUE WIRE
- DC VOLTAGE READINGS ARE POSITIVE WITH RESPECT TO CHASSIS GROUND UNLESS OTHERWISE SPECIFIED.
- CIRCUIT OF CHASSIS MAY VARY SLIGHTLY FROM THAT SHOWN HERE DUE TO NORMAL PRODUCTION CHANGES.
- D7-10 ARE SILICON AX TYPE 1A 100V DIODES.



POST OFFICE BOX 310
 LINDEN, NEW JERSEY
 MODEL V-4B
 U.S. PATENT PENDING
 (REV) DATE SWG. NO. PART NO. REV
 64 57 06 700 4010267 A